

Panel Thermal Printer



WP-K617

Printing speed : 70 mm/sec

Interface : Built-in USB and RS-232C



WP-K617H



WP-K617V

Specification

Model	WP-K617H		WP-K617V
Printing method	Thermal line		
Printing speed	70 mm/sec		
Command	ESC/POS		
Driver	Linux and Windows		
Character structure	Alphanumeric (Font A)	Alphanumeric (Font B)	Kanji
	12 x 24 dots	9 x 17 dots	24 x 24 dots
Columns	32 columns	42 columns	16 columns
Character size	1.50 (W) x 3.00 (H) mm	1.13 (W) x 2.13 (H) mm	3.00 (W) x 3.00 (H) mm
Density	203 dpi		
Fonts	Multilingual code page x 46, Chinese, Japanese, Thai and Korean		
Bar code	UPC-A, UPC-E, EAN8, EAN13, Code39, Code93, Codabar, Code128 and ITF		
Detectors	Paper end, Paper near end, Printer head overheat and Cover		
Paper	Single-ply thermal paper roll		
Paper width	58 mm		
Paper thickness	0.05 ~ 0.06 mm		
Paper roll size	57.5±0.5 (W) x 50 (Dia) mm		
Printer Head Reliability	50 km		
Ext. Flash	4M bytes (NV Image)		
Power supply	+12 VDC / 3 A		
Interface	Built-in USB and RS-232C		
Weight	193 g		
Dimensions	92 (W) x 111 (D) x 80 (H) mm		92 (W) x 80 (D) x 111 (H) mm
Temperature	Operating	0 ~ 45°C	
	Storage	-20 ~ 60°C	
Humidity	Operating	30 ~ 85 %RH	
	Storage	10 ~ 90 %RH	