

Portable Thermal Printer



WP-P1000

Interface : Bluetooth and USB

Printing speed : 100 mm/sec



Barcode QR code



Accessory



Holster



Battery charger



Battery



USB Cable



USB power adapter

Specification

Printing method	Thermal line		
Printing speed	100 mm/sec		
Command	ESC/POS		
Driver and SDK	Windows and Android SDK		
Character structure	Alphanumeric (Font A)	Alphanumeric (Font B)	Kanji
	12 x 24 dots	9 x 17 dots	24 x 24 dots
Columns	32 columns	42 columns	16 columns
Character size	1.50 (W) x 3.00 (H) mm	1.13 (W) x 2.13 (H) mm	3.00 (W) x 3.00 (H) mm
Density	203 dpi		
Fonts	Multilingual code page x 46, Chinese, Japanese, Thai and Korean		
Bar code	UPC-A, UPC-E, EAN13, EAN8, Code39, Code93, Codabar, Code128, ITF and QR code		
Detectors	Paper end, Printer head overheat, Black mark and Cover		
Paper	Single-ply thermal paper roll, Label paper and Black mark paper		
Paper width	58 mm		
Paper thickness	0.06 ~ 0.12 mm		
Paper roll size	57.5±0.5 (W) x 40 (Dia) mm		
Printer Head Reliability	50 km or more		
Ext. Flash	4M bytes		
Power supply	7.4 V (1200mAh); Charge method: USB 5V / 1A		
Interface	Bluetooth Classic (BR/EDR) and USB		
Weight	250 g (including battery)		
Dimensions	79.0 (W) x 122.8 (D) x 52.2 (H) mm		
Temperature	Operating	0 ~ 45°C	
	Storage	-20 ~ 60°C	
Humidity	Operating	10 ~ 90 %RH	
	Storage	10 ~ 90 %RH	